



SoundEar®3 – back



External microphone.



USB key for export of data.

SoundEar®3

Measure, monitor and manage
the noise with SE3-320



SoundEar®3 software

SoundEar®3 – 320 Specifications

Parameters:	Measures 3 measurements simultaneously LAF; LAS; LCpeak; Laeq 1s, Laeq 1/4 h, Laeq 1/2h, Laeq 1 h.
Resolution:	0,1 dB for all parameters
Measuring Ranges:	RMS: Total 30 – 120 dB
Deviation:	+/- 0,5 dB
Frequency Range:	20Hz- 20 kHz
Frequency Weightings:	A- weighting (RMS), C-weighting (Peak) Slow(1S) & Fast (125 ms)
Time Weighting:	90 dB and peak detection
Dynamic Range:	0-10 V or 4-20 mA
2 x outputs:	Micro USB (power & PC) , USB OTG (Log, configuration)
2 xUSB outputs:	5VDC (Micro USB) / 24VDC (Screw terminal)
Power Supply:	max 2,5 W
Current Consumption:	16 MB(128 Mbit)
Internal memory:	(5-90 days log time, depending on log settings)

Real Time Clock:	Hi-precision type with battery backup (CR2032)
Microphone:	20 Hz- 20 kHz
Measurement 320:	Length: 150mm, Width: 120mm, Height: 45mm, Weight: 0.450 kg.
Standards:	IEC61672-2-2002, Type 2, ANSI 51,4 Type 260601-1: Medical electrical equipment- Part 1: general requirements for basic safety and essential performance. 60601-1-2_ Medical equipment – Part 1.2: General requirement – Part 1-2: General requirement for Basic safety and essential performance.
Connectivity accessories:	GSM module, 4 G module for Cloud solution

www.soundsafety.com.au

